

PASTOSOL[®] NTZ

anionic surfactant

| | |
|--------------------|-------------------------------------|
| Basis: | Combination of sodium salt tensides |
| Appearance: | Clear fluid liquid |
| Charge: | Anionic |
| pH (1:10): | Approx. 6.5 |

Properties:

Using **PASTOSOL NTZ** in the main soaking of fur-industry and double-face skins;

1. Is possible to reduce the wetting time.
2. Wools and leather will become much more clean
3. Fleshing operation is clearly improved.

The hair/wool remains very soft and silky, and that avoids or reduces the felting problems.

In the case of skins that may require a second fleshing, it is better to carry out a previous washing with 1-3 gr/l. of **PASTOSOL NTZ** with water at 35°C during 30 minutes.

The post-fleshing gives a leather perfectly clean and with extremely white wool, soapy and without any rest of soiling.

After tanning, washing one time in a new bath with **PASTOSOL NTZ** cleans very well the leather and in double-face wool will show very clean and white appearance.

Application:

- 1.- In the soaking of all kind of skins, especially in Double face and fur.
- 2.- In a previous bath before fleshing.
- 3.- In tanning bath (1-2 g/l.), it keeps the wool clean and soapy. It provides cleaner leathers, helping the penetration of chrome, giving at the end smoother skins.
- 4- After the tanning, washing for to get a clean wool in fur-industry.

Safety and storage:

When handling **PASTOSOL NTZ**, normal safety precautions associated with the handling of chemicals should be observed. For more specific details please refer to our safety data sheets.

PASTOSOL NTZ can be stored for up to 18 months, if temperatures below 5 °C and above 40 °C can be avoided and if kept in a cool and dry place.

09/2016

The information given in this technical leaflet is offered in good faith and is based upon our knowledge and experience of the products used. The suitability of the products mentioned to obtain specific properties or effects are given without obligation or guarantee and should be fully tested by the end user and adapted to suit prevailing works conditions or other products which may be employed.

PASTOSOL: registered trademark of TRUMPLER